

TECHNICAL SPECIFICATIONS

- DPI: II. CAT OR. III CAT.
- CE CERTIFICATION
- NORMS: EN 397:2012 + A1+2012
- REGULATION (EU) 2016/425
- CONTROL BODY NUMBER: N°0497
- MATERIAL: PE HD "UV"
- THERMIC RESISTANCE: +50 °C -20 °C
- POINTS OF HOOK: 6/6
- INSIDE: RIBBON IN POLYESTER / PLASTIC
- HARNESS IN PE LD WITH REGULATION:
 NAPE FROM 53 TO 62 cm / AUTOMATIC
- FRONT BAND WITH SWEATBAND IN SYNTHETIC SPONGE / FABRIC
- POSSIBILITY OF PERSONALIZATION: ADHESIVE LABEL PUT IN FRONT OF THE HELMET (4 x 4 cm)

Available color choices:





The most required construction, industrial safety helmets on construction sites. Its production tradition, relatively lightweight helmet design of six-point textile or PEHD fitting, places it in the very top of the helmets tested on the market. Thirty years of tradition of production ensures constant quality and proven helmet. This is a very affordable helmet and denotes the best choice between the price/quality ratios. The helmet features an excellent six-point fitting with strong textile bands and a comfortable textile or leather lining to protect the forehead. The helmet is available with various chin protectors. It can be supplied as category II or category III 440V c.a.